Cp			UTAH OII	_ AND GAS CO	INSERVATION C	OMMISSION	Hz.	D ·	, _	· . ٦	
REMARKS: WELL LOG	ELE	CTRIC LOGS	FILE X	WATER SAND	SLOCAT	ION INSPECTED			IB. REPORT/abd		,
asslicati	on 1	sinded	11.4.6	35							
							-				
						,					
				100	•						,
	-								 		
DATE FILED 11-21											
LAND: FEE & PATENTED		EASE NO.			PUBLIC LEASE NO.		U-50	376 ·	INDIAN		
DRILLING APPROVED:	11-29	-83 - OIL									
SPUDDED IN:											
COMPLETED:		PUT TO PRODU	ICING:								
INITIAL PRODUCTION											
GRAVITY A.P.I	-										
GOR.					-						
PRODUCING ZONES:											
TOTAL DEPTH											
WELL ELEVATION. 5	23316	3 R		·				-			
DATE ABANDONED	11.4	85			n			·	 -		
FIELD: WILDC/	T. M	MILLER	H B	etter -	reatu	Rouge	Mar	2 3/86		· ·	
UNIT:					rucy	المالكية	کاللا ۱۸۰۸	1			
COUNTY: DUCHES	SNE			****				J			
WELL NO. BOUNDA	ARY FED	ERAL #1-20				 -	APT	NO. 43-	-013-30870		
LOCATION 660 I		T. FROM (N) (S) LINE,	660	' FEL	FT. FROM (E) (W)	LINE	NENE		1/4 - 1/4 SEC.	20	
					* *				· · · · · · · · · · · · · · · · · · ·		
TWP RGE	SEC	OPERATOR			TWP	RGE	SEC.	OPERATOR			
·	. —				88	17E	20	LOMAX	EXPLORATION	ON CO.	. ges

SUBMIT IN TH (Other instru

Form approved. Budget Bureau No. 42-R1425.

,	5. LEASE DESIGNATION U-50376						
APPLICATION	FOR PERMIT T	O DRILL, DEEP	PEN, OR PLUG	BACK	6. IF INDIAN, ALLOTTEE	OR TEIBE NAME	
Ia. TYPE OF WORK DRIL	L 🛛	DEEPEN 🗆	PLUG BA		7. UNIT AGREEMENT N	лм в	
b. Type of Well OIL X GAI WELL X WE	S LL OTHER		BINGLE MULT	IPLE [8. FARM OR LEASE NAI	(8)	
2. NAME OF OPERATOR					Boundar y F	ederal	
	Exploration Co	mpany			9. WELL NO.	70 × ===	
3. ADDRESS OF OPERATOR	Pay AEO2 Houst	on TV 77210			10. FIELD AND POOL	20 <u>2</u>	
4. LOCATION OF WELL (Re	Box 4503, Houst		State requirements.*)		€ndesigna	**************************************	
A4 anufaca	FNL & 660' FEL	化双环烷基 化电子电子 医二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基	NE/NE		11. SEC., T., E., M., OR. AND SURVEY OR A	BLK.	
At proposed prod. zone					의 의 의 의 의 의 의 의 의 의 의 의 의 의 의 의 의 의 의	<u>₹</u>	
	시간 (1925), (1925) , (1946) 1985 (1937) , (1987)				Section 20,		
14. DISTANCE IN MILES A	化二氯磺基甲基酚 网络人名英格兰 医二氏管肠炎 化二十分基础		er *		12. COUNTY OR PARISH		
The Control of the Co	les South of My	the contract of the contract o		1 17 NO	Duchesne OF ACRES ASSIGNED	Utah	
LOCATION TO NEAREST PROPERTY OR LEASE LI	M. DIGTANCE & BOW THOU COURT						
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1868			PROPOSED DEPTH 7000	20. RGT	TARY OR CABLE TOOLS Rotary		
21. BLEVATIONS (Show whe 5233)					February, 1		
23. .f.	1	ROPOSED CASING A	ND CEMENTING PROG	RAM			
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH		QUANTITY OF CEME	NT	
12 1/4	8 5/8	24	300	T	o Surface		
7 7/8	5 1/2	17	TD.	A	s Required		
OCT Divisi	DEIVED 3 1 1024 ON OF OIL 8 MINING		APR 198 RECEIV	ED COOK	(AP) 37		

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any. 24. 11/16/83 TITLE V.P. Drilling & Production G.L . Pruitt (This space for Federal or State office use) APPROVAL DATE PERMIT NO. ASSOCI DISTRICT MANAGER DATE 10-29-84 TITLE CONDITIONS OF APPROVAL, IF ANY:

NOTICE OF APPROVAL

CONDITIONS OF APPROVAL ATTACHED
*See This Procession on Reverse Side *See Pristructions On Reverse Side

ASO -Br of Fluid SCC

Bio 82-4211-0166

4.922

CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Company	Lomax Ex	ploration C	0.	Well No	1-20	
Location _	Sec. 20	T 8S	R 17E	Lease No.	U-50376	
Onsite Ins	pection Date	03/27/	84	_		

All lease and/or unit operations will be conducted in such a manner that full compliance is made with applicable laws, regulations (43 CFR 3100), Onshore Oil and Gas Order No. 1, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished the field representative to insure compliance.

A. DRILLING PROGRAM

All fresh water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

1. Pressure Control Equipment

Double Ram Hydraulic BOP's will be pressure tested to a minimum of 2,100 PSI. Hydril Bag type BOP will be pressure tested to a minimum of 1,500 PSI.

BOP and choke manifold systems will be consistent with API RP 53. Pressure tests will be conducted before drilling out from under all casing strings which are set and cemented in place. Blowout preventer controls will be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned. Preventers will be inspected and operated at least daily to ensure good mechanical working order, and this inspection recorded on the daily drilling report. Preventers will be pressure tested before drilling casing cement plugs.

The District Office should be notifed, with sufficient lead time, in order to have a BLM representative on location during pressure testing.

2. Casing Program and Auxiliary Equipment

Top of the cement for the long string will be at least to the top of the Green River formation.

The District Office should be notified, with sufficient lead time, in order to have a BLM representative on location while running all casing strings and cementing.

3. Mud Program and Circulating Medium

No chromate additives will be used in the mud system on Federal and Indian lands without prior BLM approval to ensure adequate protection of fresh water aquifers.

4. Coring, Logging and Testing Program

Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3164. Two copies of all logs, core descriptions, core analyses, well-test data, geologic summaries, sample description, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, fluids, and/or gases) will be submitted when requested by the authorized officer (AO).

5. Anticipated Starting Dates and Notifications of Operations

No location will be constructed or moved, no well will be plugged, and no drilling or workover equipment will be removed from a well to be placed in a suspended status without prior approval of the AO. If operations are to be suspended, prior approval of the AO will be obtained and notification given before resumption of operations.

The spud date will be reported orally to the AO within 48 hours after spudding. If the spudding occurs on a weekend or holiday, the report will be submitted on the following regular work day. The oral report will be followed up with a Sundry Notice.

In accordance with Onshore Oil and Gas Order No. 1, this well will be reported on Form 3160-6 "Monthly Report of Operations", starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report will be filed, in duplicate, to the Vernal BLM District Office, 170 South 500 East, Vernal, Utah 84078.

Immediate Report: Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be promptly reported in accordance with the requirements of NTL-3A or its revision.

If a replacement rig is contemplated for completion operations, a "Sundry Notice" (Form 3160-5) to that effect will be filed, for prior approval of the AO, and all conditions of this approved plan are applicable during all operations conducted with the replacement rig.

Should the well be successfully completed for production, the AO will be notified when the well is placed in a producting status. Such notification will be sent by telegram or other written communication, not later than 5 days following the date on which the well is placed on production.

Pursuant to NTL-2B, with the approval of the District Engineer, produced water may be temporarily disposed of into unlined pits for a period of up to 90 days. During the period so authorized, an application for approval of the permanent disposal method, along with the required water analysis and other information, must be submitted to the District Engineer.

Pursuant to NTL-4A, lessees or operators are authorized to vent/ flare gas during initial well evaluation tests, not exceeding a period of 30 days or the production of 50 MMCF of gas, whichever occurs first. An application must be filed with the District Engineer and approval received, for any venting/flaring of gas beyond the initial 30 day or authorized test period.

A schematic facilities diagram as required by 43 CFR 3162.7-2, 3162.7-3, and 3162.7-4 shall be submitted to the appropriate District Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in 43 CFR 3162.7 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with 43 CFR 3162.7-4.

A first production conference will be scheduled within 15 days after receipt of the first production notice.

No well abandonment operations will be commenced without the prior approval of the AO. In the case of newly drilled dry holes or failures, and in emergency situations, oral approval will be obtained from the AO. A "Subsequent Report of Abandonment" Form 3160-5, will be filed with the AO within 30 days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Final abandonment will not be approved until the surface reclamation work required by the approved APD or approved abandonment notice has been completed to the satisfaction of the AO or his representative, or the appropriate Surface Managing Agency.

Pursuant to Onshore Oil and Gas Order No. 1, lessees and operators have the responsibility to see that their exploration, development, production, and construction operations are conducted in a manner which conforms with applicable Federal laws and regulations and with State and local laws and regulations to the extent that such State and local laws are applicable to operations on Federal or Indian lands.

B. THIRTEEN POINT SURFACE USE PLAN

1. Location of Tank Batteries and Production Facilities

All permanent (on site for six months or longer) structures constructed or installed (including oil well pumpjacks) will be painted a flat, non-reflective, earthtone color to match the standard environmental colors, as determined by the Rocky Mountain 5 State Interagency Committee. All facilities will be painted within 6 months of installation. Facilities required to comply with 0.S.H.A. (Occupational Safety and Health Act) will be excluded.

If a tank battery is constructed on this lease, it will be surrounded by a dike of sufficient capacity to contain $1\frac{1}{2}$ times the storage capacity of the battery.

Tank batteries will be placed on the north end of the location.

All loading lines will be placed inside the berm surrounding the tank battery.

All site security guidefines identified in 43 CFR 3162.7 regulations will be adhered to.

All off-lease storage, off-lease measurement, or commingling onlease or off-lease will have prior written approval from the AO.

Gas meter runs for each well will be located within 500 feet of the wellhead. The gas flowline will be buried from the wellhead to the meter and 500 feet downstream of the meter run or any production facilities. Meter runs will be housed and/or fenced.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries. Tests for meter accuracy will be conducted monthly for the first three months on new meter installations and at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with the API standards for liquid hydrocarbons and the AGA standard for natural gas measurement.

2. Source of Construction Material:

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

Construction material will be located on lease.

3. Methods of Handling Waste Disposal

The reserve pit will be lined with plastic.

Burning will not be allowed. All trash must be contained and disposed of by a trash cage and hauled to an approved sanitary landfill.

Produced waste water will be confined to a lined pit for a period not to exceed 90 days after initial production. During the 90 day period, an application for approval of a permanent disposal method and location, along with required water analysis, will be submitted for the AO's approval. Failure to file an application within the time allowed will be considered an incident of noncompliance, and will be grounds for issuing a shut-in order.

4. Ancillary Facilities:

Camp facilities will not be required.

5. Well Site Layout

The stockpiled topsoil will be stored on the south end of the location.

Reserve pits will be fenced with a wire mesh fence and topped with at least one strand of barbed wire.

6. Plans for Restoration of Surface

Immediately upon completion of drilling, the location and surrounding area will be cleared of all debris, materials, trash and junk not required for production.

Before any dirt work to restore the location takes place, the reserve pit must be completely dry and all cans, barrels, pipe, etc. will be removed.

All disturbed areas will be recontoured to the approximate natural contours.

The stockpiled topsoil will be evenly distributed over the disturbed areas.

Prior to reseeding, all disturbed areas, including the access roads, will be scarified and left with a rough surface.

Seed will be broadcast or drilled at a time specified by the BLM. If broadcast, a harrow or some other implement will be dragged over the seeded area to assure seed coverage.

The reserve pit and that portion of the location and access road not needed for production or production facilities will be reclaimed.

Move location 75' northwest to better balance cut and fill.

7. Other Information

A private surface landowner agreement will be submitted to the Vernal District office prior to any construction.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.2.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3164.

The dirt contractor will be provided with an approved copy of the surface use plan.

A cultural resource clearance will be required before any construction begins. If any cultural resources are found during construction, all work will stop and the AO will be notified.

This permit will be valid for a period of one year from the date of approval. After permit termination, a new application will be filed for approval for any future operations.

LICATION TO APPROPRIATE WATER

47-1675

NOTE:—The information given by the following blanks should be free from explanatory matter, but when necessary, a complete supplementary statement should be made for the following page under the heading "Explanatory."

For the purpose of acquiring the right to use a portion of the unappropriated water of the State of Utah, for uses indicated by (1.2) in the proper box or boxes, application is hereby made to the State Engineer, based upon the following showing of facts, submitted in accordance with the requirements of the Laws of Utah.

1.	Irrigation $\overline{f M}$ Domestic	☐ Stockwatering ₹	Munic	ipal 🗆	Power_]	Mining] Oth	er Uses∕Xk
2.	The name of the applica	nt is <u>Joe Shie</u>	lds		*************			
3.	The Post Office address	• •						
4.	The quantity of water to							
5,	The water is to be used!	_{for} Stockwatering MajorPurp						
	other use period							
	((Ninor Purp	wse)		Vionth)	(Dav) (Month)	(Day)
	and stored each year (ff	stored) from	•••••			(Day) (Y		
c	77. 1							
	The drainage area to wh					Grave II	Hank)	
7.	The direct source of sup	ply is*						
	andrieds in reilantament				ream or other	•	•	
	which is tributary to	erted from a well, a tunnel.	or drain, the	source sh	ould be dose	nated as "Fee	Jeremannal	Water" in the
space may diver	space and the renviring spaces strong its name, it named, and it sink, evaporate, or be diverted the differ the diverted to th	iould be left blank, if the s in the remaining spaces, des selore reaching said channe signated as a stream and no	source is a str signate the str els. If water f La spring.	cam, a spr cam cham rom a spn	ing, a spring, icls to who 'c ng flows in a	area, or a dfan it is tributary natural surta	n, so indica -, even tho ce channel	ate in the first nigh the water ! before being
Wes	The point of diversion from the 400 ft. South 200							
*****	(35 M	iles SW of Myton)) 					••••••
• • • • • •	*Nate . The mint of down	and builting and different of the	1					
west at a	*Note, The point of diversion in with reference to a United States greater distance, to some promin sion is not defined definitely.	cland survey corner or Umite	al States mun	gal mounn	nent it within	radistance of	sax miles o	oteither oris
9.	The diverting and carrying	ng works will consist	of <u>a co</u>	llesti	on Ditcl	i to plac	eofu	ıse
10	If water is to be stored,	aive conscity of room						
	area inundated in acres	legal so	abdivision	of area	inundated			
NE.	If application is for irrig. 4SE's Sec. 15, T4S,R2's	i, USBAM	gal subdiv	isions o	f the area	irrigated ar	e as fol	lows:
•••••	Is the land owned by the		••••••••••••••••••••••••••••••••••••••		T		(4)	
		• •			•	•	•	
13.	Is this water to be used s	• • •		r rights:	'Yes	No		-
	If "yes," identify other v				• .			•
l't.	If application is for power	er purposes, describe	•			•		
15.	If application is for mini	ng, the water will be	used in	.		· · · · · · · · · · · · · · · · · · ·	Mining	District at
16.	If application is for stock	kwatering purposes, i						
	ND ₃ SE ₄ Sec. 15, 748,					· · · · · · · · · · · · · · · · · · ·		
17. 10	If application is for dom If application is for mun	icinal amazaran arasa	er or perse	ліх н		r rannues .	••••••	
10.	If application is for other	e man industrument	a Or munic A Alemainai	panty	1			
19.	ir appacation is for othe	t uses, menide genera	u descripti	où or bi	anosed us			
20.	Give place of use by lega- graphs 14 to 19, incl	! subdivision of the ! used in Myton Oil				or all uses e Ley	lescri ^t ie	d in para-
2!.	The use of water as set feet of water and No stream or source at a pe	one second	ion will co feet and/ ows:	onsume ₋ or acre	.015 Feet wi!	l be returi	Heet ar ied to t	id/or acre- he natural

EXPLANATORY

		. • • • • • • • • • • • • • • • • • • •	. * 	The state of the s
				e - v von der ter melle til en suntregens (propogationistissis)
		an and a complete and		
		mana canada an		
		- Marie de M		
		de a destructiva de catala de la		
			**************************************	The state of the second st
	er ar transmitter a stage of the last of a stage of the last of th			
and service of management of the service of the ser		A COMMISSION OF CHAPT OF THE PARTY OF THE PA		a to Company on the Assessment of the Assessment
		er dem die de de en		
			-	
			Management of the second section is a second	
		e in a distribution of the second		
phinippengalith delendades a de estessados a e e a e e e e e e e e e e e e e e e		THE REPORT OF THE THE TAX AND A STATE OF TAX AND A STATE		
		e der til bidde værrete i te se rekilde blemske megsend getsk i å v	***************************************	
		A		A
			Committee of the Commit	
			THE RESERVE TO THE RESERVE THE STREET OF THE	
,				to an an anti-desirable community of the state of the sta
		Porties when ships this we if you are write any summinus or suppress and additionals accomplishing representa-		CAN THE STATE OF T
			- em reason con agricultura en esta de extreme de adoptica de agricultura en esta en esta en esta en esta en e	
The state of the s				manap garbillos risti umanpang upag up d r d
			······································	
	(Use page 4 if	additional explanatory	is needed.)	
The qua	intity of water sough can be beneficially us	t to be appropriated sed for the purpose	is limited to that which	ch .
		100	(Xhull	, ,
			Signature of Applican	10
y its pro per officer, or in e listed. If a corporation	the name of the partners	ship by one of the partn davit below need not be	e the name of such corpora ers, and the names of the filled in. If there is more Application.	other partners shal
	DECLADA	ATION OF CITIZEN	Jenn	
STATE OF UTAH, U.	4.1			
On the	to of the the shine and	May		peared before me, of the United States
or has declared his intenti My commission expires:	on the come that any	1/4	rodor Baldi	

.....

22. Proof of Appropriation submitted.

23. Certificate of Appropriation, No., issued


Application No. 57707

Form approved. Budget Bureau No. 42-R1425.

5. LEASE DESIGNATION AND SERIAL NO.

UNITED STATES DEPARTMENT OF THE INTERIOR

U-50376 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK 7. UNIT AGREEMENT NAME DEEPEN [PLUG BACK DRILL X b. TYPE OF WELL SINGLE ZONE MULTIPLE WELL X S. FARM OR LEASE NAME OTHER ZONE 2. NAME OF OPERATOR Boundary Federal Lomax Exploration Company 9. WELL NO. 3. ADDRESS OF OPERATOR 1-20 P.O. Box 4503, Houston, TX 77210 10. FIELD AND POOL, OR WILDCAT 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*) Undesignated ν 660' FNL & 660' FEL NE/NE 11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA At proposed prod. zone Section 20, T8S, R17E 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE* 12. COUNTY OR PARISH | 13. STATE 11 miles South of Myton, Utah Duchesne Utah 15. DISTANCE FROM PROPOSED 16. NO. OF ACRES IN LEASE 17. NO. OF ACRES ASSIGNED LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to Bearest drig. unit line, if any) TO THIS WELL 934 1705.6 19. PROPOSED DEPTH 18. DISTANCE FROM PROPOSED LOCATION® 20. ROTARY OR CABLE TOOLS TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1868 7000 Rotary 21. ELEVATIONS (Show whether DF, RT, GR, etc.) 22. APPROX. DATE WORK WILL START* 5233' GR February, 1984 S. . . PROPOSED CASING AND CEMENTING PROGRAM SIZE OF HOLE BIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 12 1/4 8 5/8 24 300 To Surface TD As Required



preventer program,		repen direction	ally, give pert	inent data on	subsurface location	ons and measured	and true vertice	al depths. Give blowo
SIGNED	Jung	G.L.	<u>Pruitt</u>	TITLE V.P.	Drilling	& Producti	ON DATE	11/16/83
(This space for	Federal or Sta	te office use)			PPROVAL DATE			
APPROVED BY				TITLE			DATE	

T 8 S, R 17 E, S.L.B. & M.

S89°54'W 80.12 660 BOUNDARY FED. #1-20 Elev. Ungraded Ground - 5233' 80.08 S89 0 56 W

X = Section Corners Located

PROJECT

LOMAX EXPLORATION CO.

Well location, BOUNDARY
FED. # 1-20, located as shown
in the NE 1/4 NE 1/4 Section 20,
T 8 S, R 17 E, S.L.B.& M. Duchesne
County, Utah.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR REGISTRATION Nº 2454

UINTAH ENGINEERING & LAND SURVEYING
POBOX Q - 85 SOUTH - 200 EAST
VERNAL, UTAH - 84078

SCALE	J" = 1000'		DATE	10/26	/83	
PARTY	D.B. B.K.	S.B.	REFER	ENCES GLO	Plat	
WEATHE	R Cold		FILE	LOMA	×	

TEN POINT WELL PROGRAM

LOMAX EXPLORATION COMPANY Boundary Federal #1-20 NE/NE Section 20, T8S, R17E Duchesne County, Utah

GEOLOGIC SURFACE FORMATION:

Uinta formation of Upper Eocene Age

2. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:

Uinta Green River Wasatch 0 - 2714 2714 5744

3. ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:

Green River

5155 - 0il

4. PROPOSED CASING PROGRAM:

8 5/8", J-55, 24#; set at 300' 5 1/2", J-55, 17#; set at TD All casing will be new

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

The operators minimum specifications for pressure control equipment are as follows:

A 10" Series 900 Hydril Bag type BOP and a 10" Double Ram Hydraulic unit with a closing unit will be utilized. Pressure tests of BOP's to 1000# will be made prior to drilling surface plug and operation will be checked daily. (See exhibit A)

6. TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:

It is proposed that the hole be drilled with fresh water to the "J" zone and with mud thereafter. The mud system will be a water based gel-chemical, weighted to 10.0 ppg as necessary for gas control.

7. AUXILIARY SAFETY EQUIPMENT TO BE USED:

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. TESTING, LOGGING AND CORING PROGRAMS:

No coring or drill stem testing has been scheduled for this well. The logging will consist of a Dual Induction Laterolog and a Compensated Neutron-Formation Density.

9. ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE:

It is not anticipated that abnormal pressures or temperatures will be encountered; nor that any other abnormal hazards such as H₂S gas will be encountered in this area.

10. ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:

It is anticipated that operations will commence approximately February, 1984.

LOMAX EXPLORATION

13 Point Surface Use Plan

For

Well Location

Boundary Federal #1-20

Located In

Section 20, T8S, R17E, S.L.B. & M.

Duchesne County, Utah

1. EXISTING ROADS

See attached Topographic Map "A".

To reach LOMAX EXPLORATION well location site Boundary Federal #1-20, located in the NE 1/4 NE 1/4 Section 20, T8S, R17E, S.L.B.& M., Duchesne County, Utah:

Proceed Westerly out of Vernal, Utah along U.S. Highway 40 - 49.0 miles to the Junction of this Highway and Utah State Highway 53; proceed Southerly along Utah State Highway 53 - 1.6 miles to its junction with Utah State Highway 216; proceed Southerly along State Highway 216 - 5.9 miles to its junction with an existing dirt road to the East; proceed Easterly along this road 1.9 miles to its junction with an existing dirt road to the North; proceed Northerly along this road 0.4 miles to its junction with the proposed access road (to be discussed in item #2).

The highways mentioned in the foregoing paragraph are bituminous surfaced roads to a point where Highway 216 exists to the South; thereafter the road is constructed with existing materials and gravels. The highways are maintained by Utah State road crews. All other roads are maintained by County crews.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing areas they are located in, and range from clays to a sandy-clay shale material.

The roads that are required for access during the drilling phase, completion phase, and production phase of this well will be maintained at the standards required by the B.L.M. or other controlling agencies. This maintenance will consist of some minor grader work for smoothing of road surfaces and for snow removal.

2. PLANNED ACCESS ROAD

See Topographic Map "B".

The planned access road leaves the existing location described in Item #1 in the NE 1/4 NE 1/4 Section 20, T8S, R17E, S.L.B.& M., and proceeds in a Easterly direction approximately 350' + to the proposed location site.

The proposed access road will be an 18' crown road (9' either side of the centerline) with drain ditches along either side of the proposed road where it is determined necessary in order to handle any run-off from normal meterological conditions that are prevalent to this area.

Back slopes along the cut areas of the road will be 1 1/2 to 1 slopes and terraced.

There will be no culverts required along this access road.

There will be no turnouts required along this road.

There are no fences encountered along this proposed road. There will be no new gates or cattleguards required.

The lands involved in this action are under B.L.M. jurisdiction.

The terrain that is traversed by this road is relatively flat. The grade of this road will not exceed 8%.

3. LOCATION OF EXISTING WELLS

There are four known existing wells within a one mile radius of this location site. (See Topographic Map "B").

4. LOCATION OF EXISTING AND PROPOSED FACILITIES

There are four existing LOMAX EXPLORATION wells within a one mile radius of this location site.

A tank battery site will be set up at the proposed location site. This battery will be used to contain production from this well. If in the event this battery can not be improvised, a flowline will be built which will extend to an existing battery in the area.

The area will be built if possible, with native materials and if these materials are not available then the necessary arrangements will be made to get them from private sources. These facilities will be constructed using bulldozers, graders and workman crews to construct and place the propsed facilities. If there is any deviation from the above, all approporiate agencies will be notified. Rehabilitation of disturbed areas no longer needed for operation after construction is completed will meet the requirements of Item #10.

5. LOCATION AND TYPE OF WATER SUPPLY

See Topographic Map "B".

At the present time, it is anticipated that the water for this well will be hauled by truck from a private water source that is indicated on Topo. Map "A".

In the event that this source is not used an alternate source will be used and all necessary arrangements will be made with the proper authorities.

There will be no water well drilled at this location site.

6. SOURCE OF CONSTRUCTION MATERIALS

All construction material for this location site and access road shall be borrow material accumulated during construction of the location site and access road. No pit lining materials from other sources are anticipated at this time, but if they are required, the appropriate actions will be taken to acquire them from private sources.

7. METHOD OF HANDLING WASTE DISPOSAL

See Location Layout Sheet.

A reserve pit will be constructed.

The reserve pit will vary in size and depth according to the water table at the time drilling.

One half of the reserve pit will be used as a fresh water storage area during the drilling of this well and the other one half will be used to store non-flammable materials such as cuttings, salts, drilling fluids, chemicals and produced fluids, etc.

If deemed necessary by the agencies concerned to prevent contamination to surrounding areas, the reserve pits will be lined with a gel.

The pits will have wire and overhead flagging installed if deemed necessary to protect the water fowl, wildlife, and domestic animals.

At the onset of drilling, the reserve pit will be fenced on three sides and at the time drilling activities are completed, it will be fenced on the fourth side and allowed to dry completely prior to the time that backfilling and other reclamation activities are attempted.

When the reserve pit dries and reclamation activities commence, the pits will be covered with a minimum of four feet of soil and all requirements in Item #10 will be followed.

A portable chemical toilet will be provided for human waste.

8. ANCILLARY FACILITIES

There are no ancillary facilities planned for at the present time and none forseen in the near future.

9. WELL SITE LAYOUT

See attached Location Layout Sheet.

The B.L.M. District Manager shall be notified before any construction begins on the proposed location site.

As mentioned in Item #7, the pits will be unlined unless it is determined by the representatives of the agencies involved that the materials are too porous and would cause comtamination to the surrounding area; then the pits will be lined with a gel and any other type of material necessary to make it safe and tight.

When drilling activities commence, all work shall proceed in a neat and orderly sequence.

10. PLANS FOR RESTORATION OF SURFACE

As there is some topsoil on the location site, it shall be stripped Page 3

and stockpiled. (See Location Layout Sheet). When all drilling and production activities have been completed, the location site and access road will be reshaped to the original contour and stockpiled topsoil spread over the disturbed area.

Any drainages re-routed during construction activities shall be restored to their original line of flow as near as possible. Fences around pits are to be removed upon completion of drilling activities and all waste being contained in the trash basket shall be hauled to the nearest Sanitary Landfill.

Restoration activities shall begin within 90 days after completion of the well. Once restoration activities have begun, they shall be completed within 30 days.

When restoration activities have been completed, the location site shall be reseeded with a seed mixture recommended by the surface owner when the moisture content of the soil is adequate for germination. The Lessee further convenants and agrees that all of said clean-up and restoration activities shall be done and performed in a diligent and most workmanlike manner and in strict conformity with the above mentioned Items #7 and #10.

11. OTHER INFORMATION

The Topography of the General Area - (See Topographic Map "A").

The area is a large basin formed by the Uinta Mountains to the North and the Book Cliff Mountains to the South. The Green River is located approximately 16 miles to the South of the location site.

The basin floor is interlaced with numerous canyons and ridges formed by the non-perennial streams of the area. The sides of these canyons are steep and ledges formed in sandstone ledges, conglomerate deposits, and shale are common in this area.

The geologic structures of the area that are visible are of the Uintah formation (Eocene Epoch) Tertiary Period in the upper elevations and the cobblestone and younger alluvial deposits from the Quaternary Period.

Outcrops of sandstone ledges, conglomerate deposits and shale are common in this area.

The topsoils in the area range from a light brownish-gray sandy clay (SM-ML) type soil with poorly graded gravels to a clayey (OL) soil.

The majority of the numerous washes and draws in the area are of non-perennial nature flowing during the early spring run-off and heavy rain storms of long duration which are rare as the normal annual rainfall in the area in only 8".

Due to the low precipitation average, climatic conditions and the marginal types of soils, the vegatation that is found in the area is common of the semi-arid regions and consists of areas of sagebrush, rabbitbrush some grasses and cacti as the primary flora. This is also true of the lower elevations.

. The fauna of the area consists predominantly of the mule deer, pronghorn antelope, coyotes, rabbits and varieties of small ground squirrels and other types of rodents. The area is used by man for the primary purpose of grazing domestic livestock.

The birds of the area are raptors, finches, ground sparrows, magpies, crows, and jays.

The Topography of the Immediate Area - (See Topographic Map "B")

Boundary Federal #1-20 is located approximately 3.0 miles North of Castle Peak Draw a non-perennial drainage which runs to the North and East. The ground slopes through the location from the Southeast to the Northwest at approximately 4.8% grade.

The vegetation in the immediate area surrounding the location site consists of hay fields, sagebrush and grasses.

There are no occupied dwellings or other facilities of this nature in the general area.

There are no visible archeological, historical or cultural sites within any reasonable proximity of the proposed location site. (See Topographic Map "B".)

12. LESSEE'S OR OPERATOR'S REPRESENTATIVE

Jack Pruitt LOMAX EXPLORATION 333 North Belt East , Ste. 880 Houston, TX 77060


1-713-931-9276

13. CERTIFICATION


I hereby certify that I, or persons under my direct supervision have inspected the proposed drill site and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are to the best of my knowledge true and correct; and that the work associated with the operation proposed herein will be performed by LOMAX EXPLORATION and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.


Date/ 1/83


Jack Pruitt



BOUNDARY FEDERAL #1-20 LOCATION LAYOUT & CUT SHEET







OPERATOR Loman	DATE 11/28/83
WELL NAME Boundary Federal #1-20	
SEC NENE 20 TO 85 R 17 E COUNTY	Duchesne
43-013-30870 API NUMBER	obral PE OF LEASE
POSTING CHECK OFF:	
INDEX	HL
NID	PI
PROCESSING COMMENTS:	CTATÉ
NO OIL WELLS WITHIN 1000 APPROVED OF UTAH	BY THE STATE DIVISION OF AND MINING 1-29-63
OIL, GAS,	AND MINING 1-29-63
DATE:	W.
CHIEF PRIROLEUM ENGINEER REVIEW:	
APPROVAL LETTER:	
SPACING: A-3 UNIT c-3	CAUSE NO. & DATE
c-3-b	3 - c
SPECIAL LANGUAGE:	

ź

7	RECONCILE WELL NAME AND LOCATION ON APD AGAINST SAME DATA ON PLAT MAP.
V	AUTHENTICATE LEASE AND OPERATOR INFORMATION
	VERIFY ADEQUATE AND PROPER BONDING
V	AUTHENTICATE IF SITE IS IN A NAMED FIELD, ETC.
	APPLY SPACING CONSIDERATION
	ORDER
	UNIT
	c-3-b
	c-3-c
V	CHECK DISTANCE TO NEAREST WELL.
	CHECK OUTSTANDING OR OVERDUE REPORTS FOR OPERATOR'S OTHER WELLS.
V	IF POTASH DESIGNATED AREA, SPECIAL LANGUAGE ON APPROVAL LETTER
V	IF IN OIL SHALE DESIGNATED AREA, SPECIAL APPROVAL LANGUAGE.
4	VERIFY LEGAL AND SUFFICIENT DRILLING WATER

November 30, 1983

Lomax Exploration Company P. O. Box 4503 Houston, Texas 77210

> RE: Well No. Boundary Federal 1-20 NENE Sec. 20, T. 8S, R. 17E 660' FNL, 660' FEL Duchesne County, Utah

Gentlemen:

Insofar as this office is concerned, approval to drill the above referred to oil well is hereby granted in accordance with Rule C-3(b), General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

RONALD J. FIRTH - Chief Petroleum Engineer

Office: 533-5771 Home: 571-6068

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-013-30870.

Sincerely,

Norman C. Stout Administrative Assistant

NCS/as cc: Branch of Fluid Minerals Bureau of Indian Affairs Encl.

Purpose of Land Management Vernal District Office 170 South 560 East Vernal Management

3162.35 U-820 U-50376

November 4, 1985

Lomax Exploration Company 50 West Broadway #1200 Salt Lake City, UT 84101

RE: Rescind Application for Permit to Drill Well No. 1-20 Section 20, TaS, R17E Duchesne County, Utah Lease No. U-50376

The Application for Permit to Drill the referenced well was approved on October 30, 1984. Since that date, no known activity has transpired at the approved location. Under current District policy, Applications for Permit to Drill are effective for a period of one year. In view of the foregoing, this office is rescinding the approval of the referenced application without prejudice. If you intend to drill at this location at a future date, a new Application for Permit to Drill must be submitted.

This office requires a letter confirming that no surface disturbance has been made for this drill site. Any surface disturbance associated with the approved location of this well is to be rehabilitated. A schedule for this rehabilitation must be submitted to this office. Your cooperation in this matter is appreciated.

Sincerely,

Craig M. Hansen ADM for Minerals

mh

bcc: State Div. 0 G & M

well file U-922/943



355 W. North Temple • 3 Triad Center • Suite 350 • Salt Lake City, UT 84180-1203 • 801-538-5340

November 21, 1985

Lomax Exploration Company 50 West Broadway #1200 Salt Lake City, Utah 84101

Gentlemen:

Re: Well No. Boundry Federal 1-20 - Sec. 20, T. 8S., R. 17E., <u>Duchesne County</u>, Utah - API #43-013-30870

In concert with action taken by the Bureau of Land Management, November 4, 1985, approval to drill the above referenced well is hereby rescinded.

A new "Application for Permit to Drill" must be filed with this office, for approval, prior to future drilling of the subject location.

Sincerely,

John R. Baza \
Petroleum Engineer

Flore Charles Com

pk

cc: Dianne R. Nielson Ronald J. Firth

File

1705/46